Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

ON Semiconductor™

General Purpose Transistor
PNP Silicon

MPS3906



CASE 29–04, STYLE 1
TO–92 (TO–226AA)



MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	V_{CEO}	–40	Vdc
Collector–Base Voltage	V_{CBO}	–40	Vdc
Emitter–Base Voltage	V_{EBO}	–5.0	Vdc
Collector Current — Continuous	I_C	–200	mAdc
Total Device Dissipation @ T_A = 25°C Derate above 25°C	P_D	625 5.0	mW mW/°C
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	1.5 12	Watts mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	–55 to +150	°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	200	°C/W
Thermal Resistance, Junction to Case	$R_{\theta JC}$	83.3	°C/W

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector–Emitter Breakdown Voltage[1] (I_C = –1.0 mAdc, I_B = 0)	$V_{(BR)CEO}$	–40	—	Vdc
Collector–Base Breakdown Voltage (I_C = –10 μAdc, I_E = 0)	$V_{(BR)CBO}$	–40	—	Vdc
Emitter–Base Breakdown Voltage (I_E = –10 μAdc, I_C = 0)	$V_{(BR)EBO}$	–5.0	—	Vdc
Collector Cutoff Current (V_{CE} = –30 Vdc, $V_{EB(off)}$ = –3.0 Vdc)	I_{CEX}	—	–50	nAdc
Base Cutoff Current (V_{CE} = –30 Vdc, $V_{EB(off)}$ = –3.0 Vdc)	I_{BL}	—	–50	nAdc

1. Pulse Test: Pulse Width = 300 μs; Duty Cycle = 2.0%.

© Semiconductor Components Industries, LLC, 2001

March, 2001 – Rev. 2
Publication Order Number:
MPS3906/D

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Max	Unit
ON CHARACTERISTICS[1]				
DC Current Gain	h_{FE}			—
(I_C = –0.1 mAdc, V_{CE} = –1.0 Vdc)		60	—	
(I_C = –1.0 mAdc, V_{CE} = –1.0 Vdc)		80	—	
(I_C = –10 mAdc, V_{CE} = –1.0 Vdc)		100	300	
(I_C = –50 mAdc, V_{CE} = –1.0 Vdc)		60	—	
(I_C = –100 mAdc, V_{CE} = –1.0 Vdc)		30	—	
Collector–Emitter Saturation Voltage	$V_{CE(sat)}$			Vdc
(I_C = –10 mAdc, I_B = –1.0 mAdc)		—	–0.25	
(I_C = –50 mAdc, I_B = –5.0 mAdc)		—	–0.4	
Base–Emitter Saturation Voltage	$V_{BE(sat)}$			Vdc
(I_C = –10 mAdc, I_B = –1.0 mAdc)		–0.65	–0.85	
(I_C = –50 mAdc, I_B = –5.0 mAdc)		—	–0.95	
SMALL–SIGNAL CHARACTERISTICS				
Current–Gain — Bandwidth Product (I_C = –10 mAdc, V_{CE} = –20 V, f = 100 MHz)	f_T	250	—	MHz
Output Capacitance (V_{CB} = –5.0 Vdc, I_E = 0, f = 1.0 MHz)	C_{obo}	—	4.5	pF
Input Capacitance (V_{EB} = –0.5 Vdc, I_C = 0, f = 1.0 MHz)	C_{ibo}	—	10	pF
Input Impedance (I_C = –1.0 mAdc, V_{CE} = –10 Vdc, f = 1.0 kHz)	h_{ie}	2.0	12	k Ω
Voltage Feedback Ratio (I_C = –1.0 mAdc, V_{CE} = –10 Vdc, f = 1.0 kHz)	h_{re}	1.0	10	X 10^{-4}
Small–Signal Current Gain (I_C = –1.0 mAdc, V_{CE} = –10 Vdc, f = 1.0 kHz)	h_{fe}	100	400	—
Output Admittance (I_C = –1.0 mAdc, V_{CE} = –10 Vdc, f = 1.0 kHz)	h_{oe}	3.0	60	μmhos
Noise Figure (I_C = –100 μAdc, V_{CE} = –5.0 Vdc, R_S = 1.0 k Ω, f = 1.0 kHz)	NF	—	4.0	dB
SWITCHING CHARACTERISTICS				
Delay Time (V_{CC} = –3.0 Vdc, $V_{BE(off)}$ = +0.5 Vdc, I_C = –10 mAdc, I_{B1} = 1.0 mAdc)	t_d	—	35	ns
Rise Time	t_r	—	50	ns
Storage Time (V_{CC} = –3.0 Vdc, I_C = –10 mAdc, I_{B1} = I_{B2} = –1.0 mAdc)	t_s	—	600	ns
Fall Time	t_f	—	90	ns

1. Pulse Test: Pulse Width = 300 μs; Duty Cycle = 2.0%.

TYPICAL NOISE CHARACTERISTICS

(V_{CE} = –5.0 Vdc, T_A = 25°C)



Figure 1. Noise Voltage



Figure 2. Noise Current

NOISE FIGURE CONTOURS

(V_{CE} = –5.0 Vdc, T_A = 25°C)



Figure 3. Narrow Band, 100 Hz



Figure 4. Narrow Band, 1.0 kHz



Figure 5. Wideband

Noise Figure is Defined as:

$$NF = 20 \log_{10}\left[\frac{e_n^2 + 4KTR_S + I_n{}^2R_S{}^2}{4KTR_S}\right]^{1/2}$$

e_n = Noise Voltage of the Transistor referred to the input. (Figure 3)
I_n = Noise Current of the Transistor referred to the input. (Figure 4)
K = Boltzman's Constant (1.38 x 10^{-23} j/°K)
T = Temperature of the Source Resistance (°K)
R_S = Source Resistance (Ohms)

TYPICAL STATIC CHARACTERISTICS



Figure 6. DC Current Gain



Figure 7. Collector Saturation Region



Figure 8. Collector Characteristics



Figure 9. “On” Voltages



Figure 10. Temperature Coefficients

TYPICAL DYNAMIC CHARACTERISTICS



Figure 11. Turn–On Time



Figure 12. Turn–Off Time



Figure 13. Current–Gain — Bandwidth Product



Figure 14. Capacitance



Figure 15. Input Impedance



Figure 16. Output Admittance



Figure 17. Thermal Response



The safe operating area curves indicate I_C–V_{CE} limits of the transistor that must be observed for reliable operation. Collector load lines for specific circuits must fall below the limits indicated by the applicable curve.

The data of Figure 18 is based upon $T_{J(pk)}$ = 150°C; T_C or T_A is variable depending upon conditions. Pulse curves are valid for duty cycles to 10% provided $T_{J(pk)} \leq$ 150°C. $T_{J(pk)}$ may be calculated from the data in Figure 17. At high case or ambient temperatures, thermal limitations will reduce the power than can be handled to values less than the limitations imposed by second breakdown.

Figure 18. Active–Region Safe Operating Area



Figure 19. Typical Collector Leakage Current

DESIGN NOTE: USE OF THERMAL RESPONSE DATA

A train of periodical power pulses can be represented by the model as shown in Figure 19. Using the model and the device thermal response the normalized effective transient thermal resistance of Figure 17 was calculated for various duty cycles.

To find $Z_{\theta JA(t)}$, multiply the value obtained from Figure 17 by the steady state value $R_{\theta JA}$.

Example:

Dissipating 2.0 watts peak under the following conditions:

t_1 = 1.0 ms, t_2 = 5.0 ms (D = 0.2)

Using Figure 17 at a pulse width of 1.0 ms and D = 0.2, the reading of r(t) is 0.22.

The peak rise in junction temperature is therefore

$\Delta T = r(t) \times P_{(pk)} \times R_{\theta JA} = 0.22 \times 2.0 \times 200 = 88°C$.

For more information, see AN–569.

PACKAGE DIMENSIONS

CASE 029–04
(TO–226AA)
ISSUE AD





SECTION X–X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. DIMENSION F APPLIES BETWEEN P AND L. DIMENSION D AND J APPLY BETWEEN L AND K MINIMUM. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.022	0.41	0.55
F	0.016	0.019	0.41	0.48
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

STYLE 1:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

NORTH AMERICA Literature Fulfillment:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada
Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com
Fax Response Line: 303–675–2167 or 800–344–3810 Toll Free USA/Canada

N. American Technical Support: 800–282–9855 Toll Free USA/Canada

EUROPE: LDC for ON Semiconductor – European Support
German Phone: (+1) 303–308–7140 (Mon–Fri 2:30pm to 7:00pm CET)
Email: ONlit–german@hibbertco.com
French Phone: (+1) 303–308–7141 (Mon–Fri 2:00pm to 7:00pm CET)
Email: ONlit–french@hibbertco.com
English Phone: (+1) 303–308–7142 (Mon–Fri 12:00pm to 5:00pm GMT)
Email: ONlit@hibbertco.com

EUROPEAN TOLL–FREE ACCESS*: 00–800–4422–3781
*Available from Germany, France, Italy, UK, Ireland

CENTRAL/SOUTH AMERICA:
Spanish Phone: 303–308–7143 (Mon–Fri 8:00am to 5:00pm MST)
Email: ONlit–spanish@hibbertco.com
Toll–Free from Mexico: Dial 01–800–288–2872 for Access – then Dial 866–297–9322

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support
Phone: 303–675–2121 (Tue–Fri 9:00am to 1:00pm, Hong Kong Time)
Toll Free from Hong Kong & Singapore:
001–800–4422–3781
Email: ONlit–asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center
4–32–1 Nishi–Gotanda, Shinagawa–ku, Tokyo, Japan 141–0031
Phone: 81–3–5740–2700
Email: r14525@onsemi.com

ON Semiconductor Website: http://onsemi.com

For additional information, please contact your local Sales Representative.